


H44W-16P swing flange check valve



| select | Inquiry | PN | DN(mm) | L | D(1) | D(2) | C | g | T | t | H n- φ |
|--------|---------|------|--------|-----|------|------|----|---|-----|-------|--------|
| 1.6MPa | 15 | 130 | 95 | 95 | 65 | 45 | 14 | 2 | - | 4-14 | |
| 1.6MPa | 20 | 150 | 105 | 105 | 75 | 55 | 14 | 2 | - | 4-14 | |
| 1.6MPa | 25 | 160 | 115 | 115 | 85 | 65 | 14 | 2 | - | 4-14 | |
| 1.6MPa | 32 | 180 | 135 | 135 | 100 | 78 | 16 | 2 | - | 4-18 | |
| 1.6MPa | 40 | 200 | 145 | 150 | 110 | 85 | 16 | 2 | - | 4-18 | |
| 1.6MPa | 50 | 230 | 160 | 165 | 125 | 100 | 16 | 3 | 160 | 4-18 | |
| 1.6MPa | 65 | 290 | 180 | 185 | 145 | 120 | 18 | 3 | 177 | 4-18 | |
| 1.6MPa | 80 | 310 | 195 | 200 | 160 | 135 | 20 | 3 | 187 | 8-18 | |
| 1.6MPa | 100 | 350 | 215 | 220 | 180 | 155 | 20 | 3 | 202 | 8-18 | |
| 1.6MPa | 125 | 400 | 245 | 250 | 210 | 185 | 22 | 3 | 227 | 8-18 | |
| 1.6MPa | 150 | 480 | 280 | 285 | 240 | 210 | 24 | 3 | 263 | 8-23 | |
| 1.6MPa | 200 | 550 | 335 | 340 | 295 | 265 | 26 | 3 | 293 | 12-23 | |
| 1.6MPa | 250 | 650 | 405 | 405 | 355 | 320 | 30 | 3 | 330 | 12-25 | |
| 1.6MPa | 300 | 750 | 460 | 460 | 410 | 375 | 30 | 4 | 392 | 12-25 | |
| 1.6MPa | 350 | 850 | 520 | 520 | 470 | 435 | 34 | 4 | 430 | 16-25 | |
| 1.6MPa | 400 | 950 | 580 | 580 | 525 | 485 | 36 | 4 | 480 | 16-30 | |
| 1.6MPa | 500 | 1150 | 705 | 705 | 650 | 608 | 44 | 4 | 560 | 20-34 | |